Emu-Graph 4 Emulator CI 144/INT

The Emu-Graph 4 Emulator is for use in a prevacuum steam sterilization process operating at 134°C for 4 minutes and 121°C for 10 minutes. When exposed to steam sterilization conditions the indicator will turn from purple to green giving an integrated response and visible indication that sterilization conditions were met.





- 4 minutes at 134°C or 10 minutes at 121°C
- Sterilant specific must have steam to change
- Lead and toxic heavy metal free

Performance Characteristics

The Emu-Graph 4 spot changes color from purple to green when exposed to appropriate steam sterilization conditions.

Physical Characteristics

Dimensions: L 89mm x W 18mm

Color Change

Purple to green

Stated Values (as determined in a steam resistometer)

- 4 minutes at 134°C
- 10 minutes at 121°C

Storage

The storage conditions are printed on the product packaging. Store in the sealed bag provided

Shelf Life

24 months from date of manufacture. The expiry date is printed on the product packaging

Standards Classification

ISO 11140-1, Type 6

SteriTec Part No.

Packaging

CI 144/INT, CI 144/INT/H Emu-Graph 4 Emulator 20 bags of 250



FTP-299 Rev. F

SteriTec Products Mfg. Co., Inc., Member of the Getinge Group 74 Inverness Drive East Englewood, CO 80112 USA

www.getinge.com/steritec